# **Model Specifications** Homestead 2.0

- INTERIOR FINISH
- ~ Spraytex 1/2" Gyproc Ceilings
- ~ 100% Polyurethane Carpet in L/R and BDRMS (20' & 22' wides) ~ Vinyl Sheet Flooring In Areas Without Carpet (20' & 22' wides)
- ~ Vinyl Sheet Flooring Throughout In 16' wide homes

VERITY HOMES

- ~ Wall Finish: Decorative Vinvl Over Gyproc (VOG)
- ~ Battens On VOG Joints
- ~ Ceiling Trim: 1-1/2" Battens
- ~ Baseboards: White Profiled Moulding
- ~ Window/Door Trim: White Profiled Moulding ~ Closets: Battens throughout
- ~ Pewter Interior Door Hardware T/O w/Door Knobs
- ~ Pre-finished White Flat Interior Doors
- ~ Toggle Light Switches
- ~ Closet Rod Only In Closets
- ~ Motion Sensor Light in Walk In Pantry/Closet where applicable

## Cabinets:

- ~ Modular Cabinets | One Single Drawer Only In Kitchen
- ~ Flat Surface Cabinet Doors w/Pewter Knob Style Handles
- ~ 3" White Subway Tile Backsplash (White Grout) | No Tile Edge
- ~ Laminated Countertop
- ~ Shelf Above Fridge
- ~ Microwave Shelf In Base Cabinet
- ~ 24" Pantry Cabinet

# **KITCHEN**

- ~ Fridge: 18 CU. FT. Two Door Top Freezer White ~ Range: 30" Electric Coil Top - White
- ~ Range Hood: Two Speed, Vented To Exterior, White
- ~ Sink:Two Bowl Stainless Steel w/Two Knob Faucet Chrome

#### UTILITIES

- ~ 40 GI Electric Water Heater
- ~ Electric Furnace
- ~ 200 Amp Electric Service Panel
- ~ Electric Conduit Through Floor
- ~ Programmable Thermostat
- ~ Copper Wiring Throughout
- ~ Plumbed & Wired For Side By Side Washer And Dryer
- ~ Insulated Water Lines In W/H Cavity

  - ~ Smoke/CO Alarms w/Battery Back Up In Hallways
- ~ Smoke Alarms In All Bedrooms

- ~ Shut Off Valves at Main Supply, Water Heater and Toilets
- Series is designed to meet the Zone 7A Energy Code Requirements of the National Building Code for Saskatchewan.

# All homes are built to meet or exceed CSA A-277 specifications.

# STANDARD CONSTRUCTION

- ~ Limited Lifetime Architectural Shingles w/Underlayment
- ~ Engineered Roof Trusses
- 3.3 kPa snowload AB, SK, MB, ON | 3.4 kPa snowload BC
- ~ Nominal 4/12 Fixed Pitch
- ~ 6" Residential Eave on 4 sides
- ~ 6 MIL Poly Vapour Barrier in Ceiling and Sidewalls
- ~ White Metal Fascia
- ~ White Soffit
- ~ Flat Ceiling T/O ~8' Walls
- ~ 2 x 6 @ 24" O.C. Outside Walls
- ~ 3/8" OSB Sheathing On Inside And Outside Of Ext. Walls ~ Low Maintenance Vinvl Siding
- ~ Tubular Laminated Steel Frame: 8" (<16'x68') or 12" (>16'x68')
- ~ 2 x 10 Floor Joists (16' wide), 16" O.C. ~ I-Joist Floor (20' & 22' wide), 19.2" O.C.
- ~ T&G OSB Floor Decking; Glued And Mechanically Fastened
- ~ Insulation: R-40 Ceiling, R-22 Wall (2.1 pts Tier 2 SK), R-48 Floor
- ~ Two Weatherproof Exterior GFI Receptacle
- ~ Frost Free Tap c/w Check Valve
- ~ Airtight Protocols (4.6 points Tier 2 SK)
- ~ Exterior Pot Lights At All Exterior Doors
- Windows (1.4 U-Value | 1.8 pts Tier 2 SK | PVC Jamb | LowE):

### ~ 46x42 In Living Room; White; Sliding

- ~ 46x42 In Bedrooms; White; Sliding ~ 46x42 In Dining Area; White; Sliding
- ~ 46x42 In Kitchen Area; White; Sliding
- **Exterior Doors:**
- ~ 36" Insulated No Light Front Door c/w Peephole ~ 32" Insulated No Light Rear Door c/w Peephole
- ~ Pot Light At Each Exterior Door

### **BATH** ~ Tub/Shower: One Piece Fiberglass In All Bathrooms

- ~ Sink: White Oval, Drop In w//Two Knob Faucet Chrome
- ~ Toilet: Single Flush, Lined Tank, White
- ~ GFI Recetpacles
- ~ Dehumidistat on Main Bath Fan
- Lighting ~ Light Bulb Package
- ~ Dome Lights T/O as indicated on floorplan
- ~ Receptacle with Switch in L/R
- ~ LED Pot Lights At All Exterior Doors